



Serving Western Colorado Since 1985

OZONE PROGRAM

Maintenance Program for your spa.

EVERY TIME YOU USE YOUR SPA

- When you are finished using your spa...
- Put in 1 teaspoon of chlorine in the filter area. If you have heavy usage you may need to add extra chlorine.
- Run clean cycle (If your spa is not equipped w/ a clean cycle, run jets for 10 minutes). Close cover.

ONCE PER WEEK

- Check PH & Alkalinity with test strips (You should not get a chlorine reading because you are using such a small amount of chlorine).
- Adjust PH & Alkalinity as necessary with Spa Up or Spa Down (**only add 1oz. at a time**). Run jets for 30 minutes, then retest in 2 to 3 hours. Continue to adjust 1oz. at a time if necessary, waiting to retest in 2 to 3 hours.
- Once PH & Alkalinity are in ideal range, put in 6 tablespoons of Renew.
- Run jets **with cover off** for 30 minutes.
- Do not leave colored spas uncovered when empty.
- Add Spa Defender according to directions to prevent calcium buildup in plumbing and equipment.

ONCE PER MONTH

- Shut off power to spa. ***Note:** On the following high performance models - Vista, Envoy, and Caspian. Shut down the 20 amp breaker first, then the 30 amp breaker. **On, all other, Hot Spring/Tiger River 220 volt models** shut down the 30 amp breaker first, then 20 amp breaker and remove filters. Spray on Filter Clean. Let cleaner penetrate for 3-6 minutes. Rinse thoroughly with high pressure nozzle, and rotate filters to prolong filter life. Make sure filters are secure and power spa up. ****Note:** With the high performance models – Vista, Envoy, and Caspian flip the 30 amp breaker on first to start water circulating (bubbles coming up from bottom of spa indicates circulation). Once water is circulating flip the 20 amp breaker on. **All other, Hot Spring/Tiger River 220 volt models** flip the 20 amp breaker on first to start water circulating. Once water is circulating, flip the 30 amp breaker on.
- Clean cover with mild soap and water. Then apply 303 Protectant to save your cover from harmful UV rays and prolong covers life.

ONCE EVERY 4 MONTHS (This is the manufacturers recommended time frame).

- Drain, clean, and refill spa ***Remember to power down your spa, using the procedure mentioned above, before draining.** Clean filters thoroughly. Always refill spa by attaching prefilter (when using prefilter make sure water runs clear first, before putting in spa) to hose and insert into the gray standpipe in your filter compartment where your AG+ silver ion cartridge goes. This insures that the equipment fills up first which helps prevent airlocks.
- Replace AG+ silver ion cartridge at this time. Remember to screw all filter caps in place.
- Add entire bottle of Spa Metal Gon evenly around spa edge.
- ****Power up spa using procedure above.**
- *****Filters need to be replaced within 1 to 2 years depending on usage of spa*****